

Certification Body:



**BUREAU
VERITAS**

Bureau Veritas Australia Pty Ltd
11/500 Collins Street
Melbourne VIC, 3000
Ph: 1800 855 190
www.bureauveritas.com.au

Certificate Holder:



AQUALIGHT Cement Board
Suite 15, Bulleen Corporate
Centre
Bulleen VIC, 3105
Australia
Ph: +61 (0) 3 9404 5141
<https://aqualight.com.au/>

Certificate number: CM70214

THIS IS TO CERTIFY THAT

AQUALIGHT Cement Board

Type and/or use of product:

AQUALIGHT Cement Board is suitable for interior and exterior applications (see limitation 6 for external applications) including external cladding, flooring substrate, ceiling, and wall lining, particularly in wet and humid areas or applications where moisture resistance and a non-combustible material are required.

Description of product:

AQUALIGHT Cement Board - Fibre-reinforced cement sheeting made from a blend of cement and light aggregates reinforced with fiberglass mesh on both sides; the product is available in 3 mm-30 mm thicknesses and Nominal sheet size of 1200 x 2400 mm (Custom lengths up to 3000 mm).

COMPLIES WITH THE FOLLOWING BCA PROVISIONS AND STATE OR TERRITORY VARIATION(S)

BCA 2022 Amdt.2

	Volume One		Volume Two	
Performance Requirement(s)	B1P1(1), limited to (2)(a) limited to self-weight, (b) & (c) (excluding 3 mm, refer to limitation 3)	Structural reliability	H1P1(1), limited to (2)(a) limited to self-weight, (b) & (c) (excluding 3 mm, refer to limitation 3)	Structural reliability and resistance
Deemed-to-Satisfy Provision(s):	C2D10(6)(d)	Non-combustible building elements	H3D2(1)(d)	Fire hazard properties and non-combustible building elements
	G5D3	Protection - residential buildings	H7D4	Construction in bushfire prone areas
	G5D4, limited to S43C10	Protection - certain Class 9 buildings	9.3.4(1)(c) fire-protective covering	Horizontal projections
State or territory variation(s):	VIC G5D4(1), limited to S43C10		NSW H7D4 QLD H7D4 (3) SA H7D4 (3)	Construction in bushfire prone areas



Sam Guindi – Product Certification Manager
Bureau Veritas Australia Pty Ltd



Harley Parkes – Unrestricted Building Certifier
Jensen Hughes Pty Ltd

Date of issue: 26 June 2026

Date of expiry: 26 June 2029



Certificate of Conformity

SUBJECT TO THE FOLLOWING LIMITATIONS AND CONDITIONS AND THE PRODUCT TECHNICAL DATA IN APPENDIX A AND EVALUATION STATEMENTS IN APPENDIX B

Limitations and conditions:

1. AQUALIGHT Cement Board shall be installed in accordance with the AQUALIGHT Cement Board Installation Instructions Rev 01, dated 15 January 2026.
2. AQUALIGHT Cement Board shall be installed by suitably qualified contractors, and in accordance with the NCC, relevant Australian Standards, project specifications, and the requirements of associated system component manufacturers.
3. AQUALIGHT Cement Board thicknesses are application-specific; refer to Section A3 of this report for detailed suitability requirements.
4. AQUALIGHT Cement Board is suitable for use on buildings that comply with AS/NZS 4600:2018.
5. AQUALIGHT Cement Board is suitable for use on buildings that comply with AS/NZS 1684.2:2018 and are within the geometric building parameters in Figure 1.2 of AS/NZS 1684:
 - a. The maximum number of storeys of timber framing shall not exceed two (2);
 - b. The maximum width of a building shall be 16,000 mm, excluding eaves;
 - c. The maximum wall height shall be 3,000 mm (floor to ceiling, as measured at common external walls, i.e. not gable or skillion ends) and;
 - d. The maximum roof pitch shall be 35° (70:100).
6. AQUALIGHT Cement Board is suitable for use as a Type B (Category 2) sheet not subjected to the type-tests and are intended for internal applications and external applications where they will not be subjected to the direct action of sun, rain and/or snow.
7. The following thicknesses of AQUALIGHT Cement Board are suitable for use in buildings located within a Bushfire Prone Area when complying with limitation 6 and installed in accordance with AS3959:2018:
 - Minimum 6 mm - Bushfire Attack Level of BAL-19 or lower.
 - Minimum 10 mm - Bushfire Attack Level of BAL-40 or lower.
8. AQUALIGHT Cement Board has not been assessed for fire hazard properties.

Building classification/s:

Volume 1 – Class 2 to Class 9 buildings
Volume 2 – Class 1 and Class 10 buildings

Scope of certification: The CodeMark Scheme is a building product certification scheme. The rules of the Scheme are available at the ABCB website www.abcb.gov.au. This Certificate of Conformity is to confirm that the relevant requirements of the Building Code of Australia (BCA) as claimed against have been met. The responsibility for the product performance and its fitness for the intended use remain with the certificate holder. The certification is not transferrable to a manufacturer not listed on Appendix A of this certificate.

Disclaimer: The Scheme Owner, Scheme Administrator and Scheme Accreditation Body do not make any representations, warranties or guarantees, and accept no legal liability whatsoever arising from or connected to, the accuracy, reliability, currency or completeness of any material contained within this certificate; and the Scheme Owner, Scheme Administrator and Scheme Accreditation Body disclaim to the extent permitted by law, all liability (including negligence) for claims of losses, expenses, damages and costs arising as a result of the use of the product(s) referred to in this certificate.

APPENDIX A – PRODUCT TECHNICAL DATA

A1 Type and intended use of product

Refer above.

A2 Description of product

Refer above.

A3 Product specification

Further product specification details are available in:

- AQUALIGHT Cement Board Product Catalogue, Revision 01, dated 15 January 2026.
- AQUALIGHT Cement Board Capability Statement, Revision 01, dated January 2026.
- AQUALIGHT Installation Instruction, Revision 01, dated 15 January 2026.
- AQUALIGHT Cement Board Technical Data Sheet, Revision 01, dated 15 January 2026.

Product	Floor Lining	Interior Lining (Class 1 and 10 only)	Ceiling Lining	Exterior Cladding (in accordance with limitation 6)
AQUALIGHT™ 3 mm decorative lining, internal applications only, self-weight only, no imposed load.	-	-	-	-
AQUALIGHT™ 6 mm	-	Yes	Yes	-
AQUALIGHT™ 8 mm	-	Yes	Yes	Yes
AQUALIGHT™ 10 mm	-	Yes	Yes	Yes
AQUALIGHT™ 12 mm	-	Yes	Yes	Yes
AQUALIGHT™ 16 mm	Yes	Yes	Yes	Yes
AQUALIGHT™ 18 mm	Yes	Yes	-	Yes
AQUALIGHT™ 20 mm	Yes	Yes	-	Yes
AQUALIGHT™ 25 mm	Yes	Yes	-	Yes
AQUALIGHT™ 30 mm	Yes	Yes	-	Yes

Refer to B2 of this report for Oranik Consulting Engineers AQUALIGHT Cement Board Span Tables issued 19th March 2026 and AQUALIGHT Cement Board – CodeMark Certificate CM70214 – Engineering Assessment for Additional Thicknesses for FC cladding and flooring dated 2nd June 2026 for further information.

A4 Manufacturer and manufacturing plant(s)

Head office - AQUALIGHT Cement Board Suite 15, Bulleen Corporate Centre Bulleen VIC, 3105 Australia. For details on manufacturing site contact the certificate holder.

A5 Installation requirements

Details on installation can be found in the following documents:

- AQUALIGHT Cement Board Installation Instructions Rev 01, dated 15 January 2026.

A6 Other relevant technical data

N/A

APPENDIX B – EVALUATION STATEMENTS

B1 Evaluation methods

BCA 2022 Amdt.2

1. Structure

A2G2(2)(a) / A5G3(1)(e) - A report from a professional engineer or other appropriately qualified person (Oranik and Intertek)

2. Non-combustibility

A2G3(2)(a)/A5G3(1)(e) - A report from a professional engineer or other appropriately qualified person (Intertek)

3. Bushfire Construction

A2G3(2)(a)/A5G3(1)(e) - A report from a professional engineer or other appropriately qualified person (Intertek)

B2 Reports

1. Oranik, AQUALIGHT Cement Board flexural and deflection checks for flooring, ceiling, and wall cladding, 19 March 2026.

This Report contains the assessment of AQUALIGHT Cement Board it provides span tables based on an assessment against AS/NZS 2908.2:2000, ASTM C1185 – 23, AS 3600:2018, AS1170.0:2002, AS1170.1:2002, AS1562.1:1992.

a. AQUALIGHT Cement Board – CodeMark Certificate CM70214 – Engineering Assessment for Additional Thicknesses for FC cladding and flooring, 2 June 2026.

This Letter includes the addition of 3 mm, 6 mm, 8 mm, 10 mm 25 mm and 30 mm AQUALIGHT Cement Boards, based on Oranik, AQUALIGHT Cement Board flexural and deflection checks for flooring, ceiling, and wall cladding dated 19 March 2026.

2. Intertek, AS 2908:2000 Cellulose-cement products Part 2: Flat Sheets, Report No. 241012001SHF-003, 14 October 2024.

This report contains the results of testing to AS 2908:2000 and demonstrates that the product meets the requirements of this standard. In addition, the report demonstrates compliance with AS3959 as a fibre-cement with a minimum thickness of 6 mm for BAL-19 and a minimum of 9 mm for BAL40.